

1206S / 1206T

Tube with Pyramid Receiver, 45mm, Stainless Steel or Titanium

The 1206S or 1206T offers a 45mm overall length pyramid receiver with tube clamp insert pylon that is compatible with tube clamps, or knees with tube clamp distal mounts.

- 45mm length, end to end
- Part Weight: 96 grams (SS) / 60 grams (Ti)
- Weight Limit: 125kg / 275lbs
- Ideal for low clearance situations requiring a pyramid receiver



1. Application

The 1206S or 1206T, Tube with Pyramid Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The 1206S or 1206T Tube with Receiver, is used to connect any pyramid system and 30mm tube clamp. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. Apply Loctite to all screws once the alignment and connection is finalized.

3. Warranty

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Environment:

Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]

Do not store in wet or very hot environment.



5. CE Conformity

This product meets the requirements Council EU 2017/1745 (MDR) for medical products. This product has been classified as a class I product according to the classification criteria outlined in appendix IX of the guidelines. Please keep this manual in safe place for future use.



Notice

Cross tighten the set screws, which are side by side, using a torque wrench set to 15 Nm.