



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1210A

Tube 910mm, Al

Weight: 538 grams
Weight Limit: 136kg / 300lbs



1210A IFU REV. E (12-15-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1210A

Tube 910mm, Al

Weight: 538 grams
Weight Limit: 136kg / 300lbs



1210A IFU REV. E (12-15-25)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1210A

Tube 910mm, Al

Weight: 538 grams
Weight Limit: 136kg / 300lbs



1210A IFU REV. E (12-15-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1210A

Tube 910mm, Al

Weight: 538 grams
Weight Limit: 136kg / 300lbs



1210A IFU REV. E (12-15-25)

1. Application

The 1210A, Aluminum Tube 910mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Tube, 910mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty

Warranty applies only when the product is used as intended without modification, following all manufacturer’s recommendations. ST&G offers 2 years warranty.

2

4. Environment:

Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F] Do not store in wet or very hot environment.

5. Declaration of Conformity

ST&G as manufacturer declares that the 1210A, Tube, 910mm, Al conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice



Tighten all the screws, which are side by side, using the torque wrench

3

1. Application

The 1210A, Aluminum Tube 910mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Tube, 910mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty

Warranty applies only when the product is used as intended without modification, following all manufacturer’s recommendations. ST&G offers 2 years warranty.

2

4. Environment:

Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F] Do not store in wet or very hot environment

5. Declaration of Conformity

ST&G as manufacturer declares that the 1210A, Tube, 910mm, Al conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice



Tighten all the screws, which are side by side, using the torque wrench

3

1. Application

The 1210A, Aluminum Tube 910mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Tube, 910mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty

Warranty applies only when the product is used as intended without modification, following all manufacturer’s recommendations. ST&G offers 2 years warranty.

2

4. Environment:

Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F] Do not store in wet or very hot environment.

5. Declaration of Conformity

ST&G as manufacturer declares that the 1210A, Tube, 910mm, Al conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice



Tighten all the screws, which are side by side, using the torque wrench

3

1. Application

The 1210A, Aluminum Tube 910mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Tube, 910mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty

Warranty applies only when the product is used as intended without modification, following all manufacturer’s recommendations. ST&G offers 2 years warranty.

2

4. Environment:

Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F] Do not store in wet or very hot environment.

5. Declaration of Conformity

ST&G as manufacturer declares that the 1210A, Tube, 910mm, Al conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice



Tighten all the screws, which are side by side, using the torque wrench

3