



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113




ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1230T

**4-Ear Connector, Solid
Pyramid, Ti**

Weight: 58 grams
Weight Limit: 170kg / 375lbs



1230T

1230T IFU REV. E (02-05-25)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113




ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1230T

**4-Ear Connector, Solid
Pyramid, Ti**

Weight: 58 grams
Weight Limit: 170kg / 375lbs



1230T

1230T IFU REV. E (02-05-25)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113




ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1230T

**4-Ear Connector, Solid
Pyramid, Ti**

Weight: 58 grams
Weight Limit: 170kg / 375lbs



1230T

1230T IFU REV. E (02-05-25)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1230T

**4-Ear Connector, Solid
Pyramid, Ti**

Weight: 58 grams
Weight Limit: 170kg / 375lbs



1230T

1230T IFU REV. E (02-05-25)

1. Application
The 1230T 4 Ear Connector, Solid Pyramid, Ti is to be stored at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

5. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

2. Description
The 4 Ear Connector, Solid Pyramid, Ti is integrated into the prosthetic socket's lamination as lamination anchor. The enclosed lamination dummy covers the pyramid during the lamination process and makes it possible to accurately fit the laminated brim. For reinforcement, tie off the individual layers of stockinette between the lamination dummy and lamination anchor.

4. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 year warranty

Tighten all the screws, which are side by side, using the torque wrench. Do not contour this component!



Notice

The type of reinforcement used depends on the type of loading expected. It generally consists of four to six layers of Nyglass, some carbon reinforcement and 1-1/2 layers of fiberglass stockinette.

6. Declaration of Conformity
ST&G as manufacturer declares that the 1230T, 4 Ear Connector, Solid Pyramid, Ti conforms to the requirements of Council EU 2017/745 (EU).

another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

3

5. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment



6. Declaration of Conformity

ST&G as manufacturer declares that the 1230T, 4 Ear Connector, Solid Pyramid, Ti conforms to the requirements of Council EU 2017/745 (EU).

ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.



Notice

Tighten all the screws, which are side by side, using the torque wrench. Do not contour this component!

warranty

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 year

2

1. Application
The 1230T 4 Ear Connector, Solid Pyramid, Ti is to be stored at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

5. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

2. Description

The 4 Ear Connector, Solid Pyramid, Ti is integrated into the prosthetic socket's lamination as lamination anchor. The enclosed lamination dummy covers the pyramid during the lamination process and makes it possible to accurately fit the laminated brim. For reinforcement, tie off the individual layers of stockinette between the lamination dummy and lamination anchor.

The type of reinforcement used depends on the type of loading expected. It generally consists of four to six layers of Nyglass, some carbon reinforcement and 1-1/2 layers of fiberglass stockinette.

4. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 year warranty

2

5. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

6. Declaration of Conformity
ST&G as manufacturer declares that the 1230T, 4 Ear Connector, Solid Pyramid, Ti conforms to the requirements of Council EU 2017/745 (EU).

another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.



Notice

Tighten all the screws, which are side by side, using the torque wrench. Do not contour this component!

3

5. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment



6. Declaration of Conformity

ST&G as manufacturer declares that the 1230T, 4 Ear Connector, Solid Pyramid, Ti conforms to the requirements of Council EU 2017/745 (EU).

ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.



Notice

Tighten all the screws, which are side by side, using the torque wrench. Do not contour this component!

3