



stngco.com

CORPORATE 10mm Offset

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1242T

10mm Offset Tube Clamp, Ti

Weight: 139grams
Weight Limit: 136kg / 300lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw : 7Nm



1242T IFU REV. A (10-10-23)



stngco.com

CORPORATE 10mm Offset

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1242T

10mm Offset Tube Clamp, Ti

Weight: 139grams
Weight Limit: 136kg / 300lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw : 7Nm



1242T IFU REV. A (10-10-23)



stngco.com

CORPORATE 10mm Offset

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1242T

10mm Offset Tube Clamp, Ti

Weight: 139grams
Weight Limit: 136kg / 300lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw : 7Nm



1242T IFU REV. A (10-10-23)



stngco.com

CORPORATE 10mm Offset

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1242T

10mm Offset Tube Clamp, Ti

Weight: 139grams
Weight Limit: 136kg / 300lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw : 7Nm



1242T IFU REV. A (10-10-23)

1. Application
The 1242T, 10mm Offset Tube Clamp, TI is to be exclusively used for the prosthetic fitting of lower extremity amputations.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2. Description
The 10mm Offset Tube Clamp, TI is used to connect any component with 30 mm tube system. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for the tube clamp. It is ideal for usage when extra alignment is needed. It is also ideal when using with pin suspension locks, where prosthetic and pin alignment can be easily adjusted using the offset clamp. The clamp design also provides versatility in that the offset position can be rotated in 360 degrees. So the offset is not just fixed linearly only in one direction, but that with rotation of the tube, the offset can be linearly set 5mm from the center in any direction. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Locate to all screws once the alignment and connection is finalized.



Notice
Tighten all the screws, which are side by side, using the torque wrench

4. Declaration of Conformity
ST&G as manufacturer declares that the 1242T, 10mm Offset Tube Clamp, TI conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

1. Application
The 1242T, 10mm Offset Tube Clamp, TI is to be exclusively used for the prosthetic fitting of lower extremity amputations.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2. Description
The 10mm Offset Tube Clamp, TI is used to connect any component with 30 mm tube system. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for the tube clamp. It is ideal for usage when extra alignment is needed. It is also ideal when using with pin suspension locks, where prosthetic and pin alignment can be easily adjusted using the offset clamp. The clamp design also provides versatility in that the offset position can be rotated in 360 degrees. So the offset is not just fixed linearly only in one direction, but that with rotation of the tube, the offset can be linearly set 5mm from the center in any direction. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Locate to all screws once the alignment and connection is finalized.



Notice
Tighten all the screws, which are side by side, using the torque wrench

4. Declaration of Conformity
ST&G as manufacturer declares that the 1242T, 10mm Offset Tube Clamp, TI conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

1. Application
The 1242T, 10mm Offset Tube Clamp, TI is to be exclusively used for the prosthetic fitting of lower extremity amputations.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2. Description
The 10mm Offset Tube Clamp, TI is used to connect any component with 30 mm tube system. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for the tube clamp. It is ideal for usage when extra alignment is needed. It is also ideal when using with pin suspension locks, where prosthetic and pin alignment can be easily adjusted using the offset clamp. The clamp design also provides versatility in that the offset position can be rotated in 360 degrees. So the offset is not just fixed linearly only in one direction, but that with rotation of the tube, the offset can be linearly set 5mm from the center in any direction. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Locate to all screws once the alignment and connection is finalized.



Notice
Tighten all the screws, which are side by side, using the torque wrench

4. Declaration of Conformity
ST&G as manufacturer declares that the 1242T, 10mm Offset Tube Clamp, TI conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

1. Application
The 1242T, 10mm Offset Tube Clamp, TI is to be exclusively used for the prosthetic fitting of lower extremity amputations.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2. Description
The 10mm Offset Tube Clamp, TI is used to connect any component with 30 mm tube system. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for the tube clamp. It is ideal for usage when extra alignment is needed. It is also ideal when using with pin suspension locks, where prosthetic and pin alignment can be easily adjusted using the offset clamp. The clamp design also provides versatility in that the offset position can be rotated in 360 degrees. So the offset is not just fixed linearly only in one direction, but that with rotation of the tube, the offset can be linearly set 5mm from the center in any direction. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Locate to all screws once the alignment and connection is finalized.



Notice
Tighten all the screws, which are side by side, using the torque wrench

4. Declaration of Conformity
ST&G as manufacturer declares that the 1242T, 10mm Offset Tube Clamp, TI conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.