



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1817T

**Linear 7mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 77 grams
Weight Limit: 170kg / 375lbs
Recommended Torque:

Socket attachment flat head screw: 10 Nm



1817T IFU REV. F (02-05-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1817T

**Linear 7mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 77 grams
Weight Limit: 170kg / 375lbs
Recommended Torque:

Socket attachment flat head screw: 10 Nm



1817T IFU REV. F (02-05-25)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1817T

**Linear 7mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 77 grams
Weight Limit: 170kg / 375lbs
Recommended Torque:
Socket attachment flat head screw: 10 Nm



1817T IFU REV. F (02-05-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1817T

**Linear 7mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 77 grams
Weight Limit: 170kg / 375lbs
Recommended Torque:
Socket attachment flat head screw: 10 Nm



1817T IFU REV. F (02-05-25)

4. Environment: Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]   5. Declaration of Conformity ST&G as manufacturer declares that the 1817T, 4 Hole Connector Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.  *Notice* All screws should have a thread locker applied and torqued to specifications. 3	1. Application The 1817T, Linear Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations. 2. Description The 4 Hole Connector Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a built in 7mm offset in linear direction to help correct misalignment for prosthetic fitting. 3. Warranty Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty. 2	1. Application Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]   5. Declaration of Conformity ST&G as manufacturer declares that the 1817T, 4 Hole Connector Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.  *Notice* All screws should have a thread locker applied and torqued to specifications. 3	1. Application The 1817T, Linear Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations. 2. Description The 4 Hole Connector Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a built in 7mm offset in linear direction to help correct misalignment for prosthetic fitting. 3. Warranty Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty. 2	4. Environment: Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]   5. Declaration of Conformity ST&G as manufacturer declares that the 1817T, 4 Hole Connector Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.  *Notice* All screws should have a thread locker applied and torqued to specifications. 3	1. Application The 1817T, Linear Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations. 2. Description The 4 Hole Connector Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a built in 7mm offset in linear direction to help correct misalignment for prosthetic fitting. 3. Warranty Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty. 2	1. Application Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]   5. Declaration of Conformity ST&G as manufacturer declares that the 1817T, 4 Hole Connector Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.  *Notice* All screws should have a thread locker applied and torqued to specifications. 3	1. Application The 1817T, Linear Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations. 2. Description The 4 Hole Connector Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a built in 7mm offset in linear direction to help correct misalignment for prosthetic fitting. 3. Warranty Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.
---	--	---	--	--	--	---	---