



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



EC REP

MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1215T

Rotating Pyramid, Ti

Weight: 42 grams

Weight Limit: 136kg / 300lbs



1215T IFU REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



EC REP

MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1215T

Rotating Pyramid, Ti

Weight: 42 grams

Weight Limit: 136kg / 300lbs



1215T IFU REV. REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



EC REP

MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1215T

Rotating Pyramid, Ti

Weight: 42 grams

Weight Limit: 136kg / 300lbs



1215T IFU REV. REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



EC REP

MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1215T

Rotating Pyramid, Ti

Weight: 42 grams

Weight Limit: 136kg / 300lbs



1215T IFU REV. D (07-11-23)

1. Application
The 1215T, Rotating Pyramid Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The rotating pyramid must be used with 1214T, 4 hole rotating base, that is connected to the socket with 4 hole thread system or with 1221S, 3 prong rotating base, that is integrated into the prosthetic socket's laminate as lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and tighten the clamp cap screw to recommended torque. The modular connection can be removed from the laminated anchor by loosening the clamp cap screw. This connection functions as rotation adjustment.

1. Application
The 1215T, Rotating Pyramid Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The rotating pyramid must be used with 1214T, 4 hole rotating base, that is connected to the socket with 4 hole thread system or with 1221S, 3 prong rotating base, that is integrated into the prosthetic socket's laminate as lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and tighten the clamp cap screw to recommended torque. The modular connection can be removed from the laminated anchor by loosening the clamp cap screw. This connection functions as rotation adjustment.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Declaration of Conformity
ST&G as manufacturer declares that the 1215T, Rotating Pyramid, Ti conforms to the requirements of Council EU 2017/745 (MDR), ST&G products are manufactured and tested for a particular lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and injury and voids any written or implied warranty, or resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Declaration of Conformity
ST&G as manufacturer declares that the 1215T, Rotating Pyramid, Ti conforms to the requirements of Council EU 2017/745 (MDR), ST&G products are manufactured and tested for a particular lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and injury and voids any written or implied warranty, or resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.



Tighten all the screws, which are side by side, using the torque wrench

1. Application
The 1215T, Rotating Pyramid Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The rotating pyramid must be used with 1214T, 4 hole rotating base, that is connected to the socket with 4 hole thread system or with 1221S, 3 prong rotating base, that is integrated into the prosthetic socket's laminate as lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and tighten the clamp cap screw to recommended torque. The modular connection can be removed from the laminated anchor by loosening the clamp cap screw. This connection functions as rotation adjustment.

1. Application
The 1215T, Rotating Pyramid Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The rotating pyramid must be used with 1214T, 4 hole rotating base, that is connected to the socket with 4 hole thread system or with 1221S, 3 prong rotating base, that is integrated into the prosthetic socket's laminate as lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and injury and voids any written or implied warranty, or resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.



Tighten all the screws, which are side by side, using the torque wrench

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Declaration of Conformity
ST&G as manufacturer declares that the 1215T, Rotating Pyramid, Ti conforms to the requirements of Council EU 2017/745 (MDR), ST&G products are manufactured and tested for a particular lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and injury and voids any written or implied warranty, or resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Declaration of Conformity
ST&G as manufacturer declares that the 1215T, Rotating Pyramid, Ti conforms to the requirements of Council EU 2017/745 (MDR), ST&G products are manufactured and tested for a particular lamination anchor. By engaging the threads from the rotating pyramid to the 4 hole rotating base or the 3 prong rotating base, adjust to desired alignment and injury and voids any written or implied warranty, or resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.



Tighten all the screws, which are side by side, using the torque wrench